

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

---

1. (Original): A transmission circuit of a mobile communication terminal device of CDMA system comprising:

code generating means for generating a multi-bit code necessary for transmission;

storing means for storing value of each bit of said code generating means; and

control means for writing value of each bit at an arbitrary timing of said code generating means, and reading the value of each bit stored in said storage means at an arbitrary timing to set to each corresponding bit of said code generating means.

2. (Original): A reception circuit of a mobile communication terminal device of CDMA system comprising:

code generating means for generating a multi-bit code necessary for reception;

storing means for storing value of each bit of said code generating means; and

control means for writing value of each bit at an arbitrary timing of said code generating means, and reading the value of each bit stored in said storage means at an arbitrary timing to set setting to each corresponding bit of said code generating means.

3. (Original): A transmission circuit as set forth in claim 1, wherein said control means comprises:

means for performing a process of transmission data with a code by continuously operating said code generating means at an initial code period after initiation of transmitting operation or modification of a transmission code, and writing a value of each bit of said code generating means in said storage means at a timing of leading end of each discontinuous transmission unit period which is shorter than a code period, in said code period;

means for reading a bit string corresponding to discontinuous transmission unit period stored in said storage means at a timing of leading end of discontinuous transmission unit period in second and subsequent code period to perform transmission and perform process of transmission data with the generation code with performing code generating operation after setting said bit storing in respectively corresponding bit of said code generating means; and

means for interrupting operation of said code generating means in the discontinuous transmission unit period not performing transmission.

4. (previously presented): A reception circuit as set forth in claim 2, wherein said control means comprises:

means for performing a process of reception data with a code by continuously operating said code generating means at an initial code period after initiation of receiving operation or modification of a reception code, and writing a value of each bit of said code generating means

in said storage means at a timing of leading end of each discontinuous reception unit period which is shorter than a code period, in said code period;

means for reading a bit string corresponding to discontinuous reception unit period stored in said storage means at a timing of leading end of discontinuous reception unit period in second and subsequent code period to perform reception and perform process of reception data with the generation code with performing code generating operation after setting said bit string in respectively corresponding bit of said code generating means; and

means for interrupting operation of said code generating means in the discontinuous reception unit period not performing reception.

5. (Original): A transmission circuit as set forth in claim 3, wherein said control means controls said code generating means to operate only in a time zone performing transmission and to interrupt the operation in a time zone not performing transmission, in discontinuous transmission.

6. (Original): A reception circuit as set forth in claim 4, wherein said control means controls said code generating means to operate only in a time zone performing reception and to interrupt the operation in a time zone not performing reception, in discontinuous reception.

7. (Original): A transmission circuit as set forth in claim 1, wherein said code generating means is a shift register of multi-bit construction.

8. (Original): A transmission circuit as set forth in claim 7, wherein said control means performs control for interrupting operation of said code generating means by performing stopping shifting operation of said shift register.

9. (Original): A reception circuit as set forth in claim 2, wherein said code generating means is a shift register of multi-bit construction.

10. (Original): A reception circuit as set forth in claim 9, wherein said control means performs control for interrupting operation of said code generating means by performing stopping shifting operation of said shift register.

11. (currently amended): A mobile communication terminal device of CDMA system comprising:

~~a transmission circuit defined in claim 1; and~~

~~a reception circuit defined in claim 2.~~

a transmission circuit comprising a first code generating circuit for generating a multi-bit code necessary for transmission, a first storing device for storing value of each bit of said first

code generating circuit, and a first control device for writing value of each bit at an arbitrary timing of said first code generating circuit, and reading the value of each bit stored in said first storage device at an arbitrary timing to set to each corresponding bit of said first code generating circuit; and

a reception circuit comprising a second code generating circuit for generating a multi-bit code necessary for reception, a second storing device for storing value of each bit of said code generating circuit, and a second control device for writing value of each bit at an arbitrary timing of said second code generating circuit, and reading the value of each bit stored in said second storage device at an arbitrary timing to set setting to each corresponding bit of said second code generating circuit.

12. (currently amended): A mobile communication terminal device as set forth in claim 11, wherein said first and second code generating means is used in circuits are the same circuit that is common to said transmission circuit and said reception circuit.

13. (currently amended): A mobile communication terminal device as set forth in claim 12, comprises:

a common shift register portion constituted of shift register having smaller bit number among registers forming respective code generating ~~means circuit~~ of said transmission circuit and reception circuit;

a remaining shift register portion constituted of remaining shift register having greater bit number among registers forming respective code generating ~~means~~circuit of said transmission circuit and reception circuit;

exclusive OR ~~means~~circuit and shift register tap for transmission and reception for generating respective of said ~~codes~~code necessary for transmission and reception;

switching ~~means~~circuit for switching respective outputs of said exclusive OR ~~means~~circuit, an output of said common shift register portion and an output of remaining shift register portion depending upon transmission and reception.

14. (currently amended): A mobile communication terminal device in a CDMA system designed for interrupting transmitting operation in a discontinuous reception unit period in a discontinuous transmission, and for interrupting receiving operation in discontinuous transmission unit period, comprising:

a common shift register portion constituted of shift register having smaller bit number among registers forming respective code generating ~~means~~circuit of said ~~a~~ transmission circuit and reception circuit;

a remaining shift register portion constituted of remaining shift register having greater bit number among registers forming respective code generating ~~means~~circuit of said transmission circuit and reception circuit;

exclusive OR ~~means-circuit~~ and shift register tap for transmission and reception for generating respective of said ~~codes~~code necessary for transmission and reception;

switching ~~means-circuit~~ for switching respective outputs of said exclusive OR ~~means~~circuit, an output of said common shift register portion and an output of remaining shift register portion depending upon transmission and reception.

B  
15. (Original): A transmission control method for a mobile communication terminal device in CDMA system having code generating means generating a multi-bit code necessary for transmission comprising:

a writing step of switching each bit of said code generating means at an arbitrary timing in a storage means; and

a reading step of reading out value of each bit stored in said storage means at an arbitrary timing and setting in each corresponding bit of said code generating means.

16. (Original): A reception control method for a mobile communication terminal device in CDMA system having code generating means generating a multi-bit code necessary for reception comprising:

a writing step of switching each bit of said code generating means at an arbitrary timing in a storage means; and

a reading step of reading out value of each bit stored in said storage means at an arbitrary timing and setting in each corresponding bit of said code generating means.

17. (currently amended): A transmission control method as set forth in claim 15, wherein said writing step comprises:

step of performing a process of transmission data with a code by continuously operating said code generating means at an initial code period after initiation of transmitting operation or modification of a transmission code, and writing a value of each bit of said code generating means in said storage means at a timing of leading end of each discontinuous transmission unit period which is shorter than a code period, in said code period;

said reading step comprises:

step of reading a bit string corresponding to discontinuous transmission unit period stored in said storage means at a timing of leading end of discontinuous transmission unit period in second and subsequent code period to perform transmission and setting said bit string in respectively corresponding bit of said code generating means;

said transmission control ~~step~~method further comprises:

step of processing transmission data with the generation code with performing code generating operation after setting said bit string in respectively corresponding bit of said code generating means; and



step of interrupting operation of said code generating means in the discontinuous transmission unit period not performing transmission.

18. (Original): A reception control method as set forth in claim 16, wherein said writing step comprises:

B  
step of performing a process of reception data with a code by continuously operating said code generating means at an initial code period after initiation of transmitting operation or modification of a reception code, and writing a value of each bit of said code generating means in said storage means at a timing of leading end of each discontinuous reception unit period which is shorter than a code period, in said code period;

said reading step comprises:

step of reading a bit string corresponding to discontinuous reception unit period stored in said storage means at a timing of leading end of discontinuous reception unit period in second and subsequent code period to perform reception and setting said bit string in respectively corresponding bit of said code generating means;

said reception control method further comprises:

step of processing reception data with the generation code with performing code generating operation after setting said bit string in respectively corresponding bit of said code generating means; and

step of interrupting operation of said code generating means in the discontinuous reception unit period not performing reception.

B1  
19. (Original): A transmission control method as set forth in claim 17, wherein said code generating means only is operated only in a time zone performing transmission and interrupts said code generating means in a time zone not performing transmission, in discontinuous transmission.

20. (Original): A reception control method as set forth in claim 18, wherein said code generating means only is operated only in a time zone performing reception and interrupts said code generating means in a time zone not performing reception, in discontinuous reception.

21. (Original): A storage medium storing a control program of a transmission control method of a mobile communication terminal device in CDMA system having code generating means for generating multi-bit code necessary for transmission,

said program comprising:

a writing step of switching each bit of said code generating means in storage means at an arbitrary timing; and

a reading step of reading value of each bit stored in said storage means at an arbitrary timing to set in each corresponding bit of said code generating means.

22. (Original): A storage medium storing a control program of a reception control method of a mobile communication terminal device in CDMA system having code generating means for generating multi-bit code necessary for reception,

said program comprising:

1  
\$ a writing step of switching each bit of said code generating means in storage means at an arbitrary timing; and

a reading step of reading value of each bit stored in said storage means at an arbitrary timing to set in each corresponding bit of said code generating means.

23. (Original): A storage medium as set forth in claim 21, wherein said writing step comprises:

step of performing a process of transmission data with a code by continuously operating said code generating means at an initial code period after initiation of transmitting operation or modification of a transmission code, and writing a value of each bit of said code generating means in said storage means at a timing of leading end of each discontinuous transmission unit period which is shorter than a code period, in said code period;

said reading step comprises:

step of reading a bit string corresponding to discontinuous transmission unit period stored in said storage means at a timing of leading end of discontinuous transmission unit period in

second and subsequent code period to perform transmission and setting said bit string in respectively corresponding bit of said code generating means;

the program further comprises:

step of processing transmission data with the generation code with performing code generating operation after setting said bit string in respectively corresponding bit of said code generating means; and

step of interrupting operation of said code generating means in the discontinuous transmission unit period not performing transmission.

24. (Original): A storage medium as set forth in claim 22, wherein said writing step comprises:

step of performing a process of reception data with a code by continuously operating said code generating means at an initial code period after initiation of transmitting operation or modification of a reception code, and writing a value of each bit of said code generating means in said storage means at a timing of leading end of each discontinuous reception unit period which is shorter than a code period, in said code period;

step of reading a bit string corresponding to discontinuous reception unit period stored in said storage means at a timing of leading end of discontinuous reception unit period in second and subsequent code period to perform reception and setting said bit string in respectively corresponding bit of said code generating means;

step of processing reception data with the generation code with performing code  
generating operation after setting said bit string in respectively corresponding bit of said code  
generating means; and

step of interrupting operation of said code generating means in the discontinuous  
reception unit period not performing reception.

25. (Original): A storage medium as set forth in claim 23, wherein said code generating  
means only is operated only in a time zone performing transmission and interrupts said code  
generating means in a time zone not performing transmission, in discontinuous transmission.

26. (Original): A storage medium as set forth in claim 24, wherein said code generating  
means only is operated only in a time zone performing reception and interrupts said code  
generating means in a time zone not performing reception, in discontinuous reception.

27. (new): The transmission circuit of claim 1, wherein the code generating means is  
started up at an arbitrary timing.

28. (new): The reception circuit of claim 2, wherein the code generating means is started  
up at an arbitrary timing.

29. (new): The device of claim 11, wherein the first and second code generating circuits are started up at an arbitrary timing.

30. (new): The transmission method of claim 15, wherein the code generating means is started up at an arbitrary timing.

31. (new): The reception method of claim 16, wherein the code generating means is started up at an arbitrary timing.

32. (new): The program of claim 21, wherein the code generating means is started up at an arbitrary timing.

33. (new): The program of claim 22, wherein the code generating means is started up at an arbitrary timing.

---

B1  
cancel